

# Wicket door

40 mm thick panels

Outside sections fitted with stylish Microline finish

Wind- and waterproof connection between the sections

Inside sections standard in RAL 9002

Exterior available in 19 standard colours at no extra charge



## 40mm wicket door

for industrial sectional door

### Properties

- maximum passage width 1,250 mm
- adjustable hinges for correct adjustment during assembly
- class 3 water penetration resistance according to EN 12425
- class 3 wind resistance according to EN 12424, wind resistant up to 11 Beaufort
- available with a 195 mm or 95 mm high threshold, or an extra-sloping, low 14.5 mm threshold that is wheelchair-friendly
- already prepared for use as an escape door
- EN 13241 compliant



# 40 mm wicket door for in an industrial sectional door

The 40 mm wicket door can be used in Alpha's Iso and Alu sectional doors. The wicket door has the same excellent thermal insulation and soundproofing properties.

Dimensions	
max. width sectional door	6,000 mm
max. height sectional door	6,000 mm
threshold height	14,5 mm / 95 mm / 195 mm
Distance to edge of sectional door	min. 500 mm

## Components and construction

The 40 mm wicket door consists of horizontal sections that exactly match the other sections of the sectional door. Even with wicket door, your sectional door can be used just as intensively. The sections of the wicket door are available as Iso or Alu panels, so that they match your sectional door or provide extra daylight.

## Materials

- thermally insulated, galvanized steel sandwich panels, insulated with polyurethane foam (CFC-free)
- panel thickness 40 mm
- top, side and bottom seal of insulating material
- seal between the panels of insulating material

## Window and panel options

- the exterior side of the panels has a microline profiling and a polyester-coating in RAL3000, RAL5003, RAL5010, RAL6005, RAL6009, RAL7005, RAL7015, RAL7016, RAL7021, RAL7022, RAL7035, RAL8014, RAL9002, RAL9005, RAL9006, RAL9007, RAL9010, Goosewing Grey or Merlin Grey. Other RAL colors available<sup>1</sup>
- the interior side of the panels has a horizontal profiling and a polyester-coating in RAL9002. Other RAL colors available<sup>1</sup>
- one or more panels constructed of anodized aluminum profiles with double acrylic, polycarbonate or Plexiglas glazing, or single-walled perforated aluminium plate in 2 variations
- various oblong window sizes available, with straight or rounded corners, containing single or double insulating glazing
- extra low burglar resistant windows or attractive round windows

## Options / accessories<sup>1</sup>

- wicket door profiles spray-painted in colour
- addition of a wicket door lock
- also available as wicket door in a sectional door with stucco profiling in 3 standard RAL colours without surcharge

## Normal locks

- lock with a door handle on both sides
- lock with a door lock cover plate on the outside and a door handle on the inside

## Panic lock when a wicket door is used as an escape door

- panic lock (panic function B) with a handle on both sides (split tumbler)
- panic lock (panic function B) with handle on the outside and push bar on the inside (split tumbler)
- panic lock (panic function E) with a door lock cover plate on the outside and a push bar on the inside
- panic lock (panic function E) with a door lock cover plate on the outside and a door handle on the inside

<sup>1</sup> subject to surcharge



## For more information:

Pittelderstraat 10  
6942 GJ Didam Netherlands  
+31 316 228066  
info@alpha-deuren.nl  
www.alpha-deuren.nl

